PORSCHE

Major Maintenance Checklist – Cayenne S/T V8 (2008)

Required Maintenance and Lubrication Service

□ Major Maintenance (Labor Operation 03 26 00 ..) See Technical Manual After 36,000, 72,000, 108,000, 144,000 miles etc. / 60,000, 120,000, 180,000, 240,000 km etc.

Note: If the mileage for scheduled maintenance is not reached, major maintenance must be performed no later than after 3, 6, 9, 12..... years.

The terms 'check' and 'inspection' include all necessary subsequent work such as adjusting, readjusting, correcting and topping off, but do not include repairing, replacing and reconditioning parts or assemblies.

	Diagnosis system: Read out fault memory; reset maintenance interval
	Underside of vehicle and engine compartment: Visual inspection for leaks (oil and fluids)
	Engine compartment: Visual inspection for damage
	Underbody covers: Visual inspection, check that all are securely fastened – replace any damaged or missing panels
	Change engine oil and oil filter
	PDCC: Check fluid level
	Air filter/s: Check the air filter condition, and if necessary, replace
	Pollen filter: Replace filter element
	Check drive belt
	Steering gear: Visual inspection of the dust boots for signs of damage
_	Tie rod ends: Check play and dust boots
	Power steering: Check fluid level
	Fuel system lines and connections: Visual inspection
_	Coolant hoses: Check condition
	Radiators and air intakes: Visual inspection for exterior debris and blockage
_	Coolant: Check level and antifreeze protection levels
	Parking brake: Check free play
	Brake system: Visual inspection of the brake pads and brake discs for signs of wear
	Brake hoses and lines: Visual inspection for damage, correct routing and corrosion Check brake fluid level
	Axle shafts: Visual inspection of the for leaks & signs of damage
	Axle joints: Check play; visual inspection of the dust boots for signs of damage
	Drive shafts: Visual inspection of the sleeves for leaks & signs of damage
	Exhaust system: Visual inspection for leaks and signs of damage; check mounts
	Tires, external spare wheel: Check condition and tire pressure
	Check firewall body drains for debris
	Lubricate door latch and fastening bolts
	Panorama roof: Adapt control module
	Windshield wiper/washer system, headlight washer: Check function, fluid level, nozzle adjustment, and antifreeze protec-
_	tion level
	Check wiper blades
	Seat belts: Check operation and condition
	Vehicle lighting: Check operation
	All headlights: Check adjustment
	Horn: Check operation
_	Batteries and ventilation hoses: Check condition
	Trailer coupling: Check operation
	Airbag system: Check operation and condition (see additional maintenance)
Ad	Iditional Maintenance – Replace Spark Plugs (Labor Operation 03 81 00)
	Replace spark plugs: Cayenne S every 36,000 miles / 60,000 km or 4 years
	Replace spark plugs: Cayenne Turbo every 24,000 miles / 40,000 km or 4 years
Ad	ditional Maintenance every 48,000 miles / 80,000 km or 6 years (Labor Operation 03 82 00)
	Replace PDCC reservoir
Ad	ditional Maintenance every 72,000 miles / 120,000 km or 4 years (Labor Operation 03 85 00)

Air filter element/s should be changed more often dependent on vehicle use and operation in dusty environments.

Air filter element/s (1 or 2 dependent on options)