

## Minor Maintenance 1 Checklist - Cayenne S/T V8 (M.Y. 2008)

Required Maintenance and Lubrication Service

☐ <b>Minor Maintenance</b> (Labor Operation 03 24 00) See Technical Manual After 12,000, 48,000, 84,000, 120,000 miles etc. / 20,000, 80,000, 140,000, 200,000 km etc.
<b>Note:</b> If the mileage for scheduled maintenance is not reached, minor maintenance 1 must be performed no later than after 1, 4, 7, 10 years.
The terms 'check' and 'inspection' include all necessary subsequent work such as adjusting, readjusting, correcting and topping off, but do not include repairing, replacing and reconditioning parts or assemblies.
☐ Diagnosis system: Read out fault memory; reset maintenance interval
<ul> <li>☐ Underside of vehicle and engine compartment: Visual inspection for leaks (oil and fluids)</li> <li>Engine compartment: Visual inspection for damage</li> <li>Underbody covers: Visual inspection, check that all are securely fastened – replace any damaged or missing panels</li> <li>☐ Change engine oil and oil filter</li> </ul>
□ PDCC: Check fluid level
Coolant hoses: Check condition
Radiators and air intakes: Visual inspection for exterior debris and blockage Coolant: Check level and antifreeze protection level
☐ Brake system: Visual inspection of the brake pads and brake discs for signs of wear
☐ Brake hoses and lines: Visual inspection for damage, correct routing and corrosion Check brake fluid level
☐ Check tightness of bolts on the suspension adjustment system at the front and rear (only applies to the first service) ☐ Tires, external spare wheel: Check condition and tire pressure
☐ Check firewall body drains for debris
<ul> <li>□ Panorama roof: Adapt control module</li> <li>□ Windshield wiper/washer system, headlight washer: Check function, fluid level, nozzle adjustment, and antifreeze protection level, check wiper blades</li> </ul>
☐ Vehicle lighting: Check operation
☐ All headlights: Check adjustment
☐ Horn: Check operation
☐ Batteries and ventilation hoses: Check condition
☐ Electrical equipment as well as indicator and warning lights: Check operation
Additional Maintenance - Replace Spark Plugs (Labor Operation 03 81 00)
Replace spark plugs: Cayenne S every 36,000 miles / 60,000 km or 4 years  Replace spark plugs: Cayenne Turbo every 24,000 miles / 40,000 km or 4 years
Additional Maintenance every 48,000 miles / 80,000 km or 6 years (Labor Operation 03 82 00)
Replace PDCC reservoir
Additional Maintenance every 72,000 miles / 120,000 km or 4 years (Labor Operation 03 85 00)  Air filter element/s should be changed more often dependent on vehicle use and operation in dusty environments.  Air filter element/s (1 or 2 dependent on options)
Additional Maintenance every 144,000 miles / 240,000 km or 16 years
<ul> <li>□ Change front differential oil</li> <li>□ Change rear differential drive oil</li> <li>□ Change transfer case oil</li> <li>□ Change manual transmission oil</li> <li>□ Change Tiptronic transmission oil and ATF filter</li> </ul>
Additional Maintenance every 2 years
Change brake fluid (use only Original Porsche Brake Fluid)
Additional Maintenance every 4 years  Replace tire sealant
Additional Maintenance every 4 years – then every 2 years
☐ Check battery for tire pressure monitoring system
Additional Maintenance after 10 years – then every 2 years  Airbag system: Check operation and condition

Inspection Performed - Technician Signature:		
Road Test Check		
Remote control, front seats, foot brake and parking brake (also operating travel), engine, clutch, steering, transmission, ParkAssist, automatic speed control, PSM switches, heater, air-conditioning system and instruments: Check operation Oils, fluids: Visual inspection for leaks		
Road Test Performed - Technician Signature:		
Customer Name:	Date:/	
VIN: WP1	<u> </u>	
Mileage (check one) 🖵 Miles 🖵 Kilometers:	<u> </u>	
Dealer Name:	Dealer Code:	
Repair Order #:		
Technician Name:		
Technician Signature:		