

Maintenance Checklist - 911 Turbo (997) (2009)

Required Maintenance and Lubrication Service (USA & Canadian Vehicles Only, Not For 911 GT2 (997), use separate checklist)

| * Oil Change Every 10,000 miles (15,000 km) or 1 year. See Below Check Box. | | |
|--|--|--|
| | Maintenance (Labor Operation 03 16 00) See Technical Manual After 40,000, 80,000, 120,000, 180,000 miles (60,000, 120,000, 180,000, 240,000 km) etc. Note: If the mileage for scheduled maintenance is not reached, maintenance must be performed no later than after 4, 8, 12 years. | |
| The terms 'check' and 'inspection' include all necessary subsequent work such as adjusting, readjusting, correcting and topping off, but do not include repairing, replacing and reconditioning parts or assemblies. | | |
| | Diagnosis system: Read fault memory; reset maintenance interval/Read and record range information on R.O. | |
| | Change engine oil and oil filter (Every 10,000 miles/15,000 km, see separate Oil Change Sheet, PNA 000 162 EF) | |
| | Vehicle underside and engine compartment: Visual inspection for leaks (oils and fluids) and abrasion (lines and hoses); Underbody panels: visual inspection for completeness, installation and damage | |
| | Coolant hoses: Check condition Radiators and air intakes: Visual inspection for external debris and blockage Coolant: Check level and antifreeze protection level | |
| | Air filter: Replace filter element | |
| | Pollen filter: Replace filter element | |
| | Fuel lines and connections: Visual inspection for damage and leaks | |
| | Brake system: Visual inspection of the brake pads and brake discs for wear | |
| | Parking brake: Check free play of parking brake lever | |
| | Brake hoses and lines: Visual inspection for damage, routing and corrosion | |
| | Steering gear: Visual inspection of the dust boots for damage | |
| | Tie rod ends: Check play and dust boots Axle joints: Check play; visual inspection of the dust boots for damage. Check the screw connections of the front and rear running gear adjustment points are secure | |
| | Drive shafts: Visual inspection of the dust boots for leaks and damage | |
| = | Exhaust system: Visual inspection for leaks and damage; check mounting and heat shields | |
| ā | Tires: Check condition and tire pressure | |
| ā | Check firewall and cabrio section body drains for debris | |
| = | Check the door, lid locks and safety hook of the front lid for secure seating and function properly | |
| $\bar{\Box}$ | Seat belts: Check function and condition | |
| $\bar{\Box}$ | Vehicle lighting: Check function | |
| _ | All headlights: Check setting | |
| | Horn: Check function | |
| | Windshield wiper/washer system, headlight washer: Check fluid level and nozzle settings (use winter antifreeze | |
| _ | protection during winter months) | |
| | Check wiper blades | |
| <u></u> | Battery: Check condition and electrolyte level | |
| | Electrical equipment, warning and indicator lights: Check function | |
| Additional maintenance for spark plugs Labor operation 03 81 00 | | |
| | | |
| | Replace spark plugs every 30,000 miles (45,000 km) or every 4 years | |
| Add | ditional maintenance for drive belt Labor operation 03 60 00 | |
| | Check drive belt at 40,000 miles (60,000 km) or every 4 years | |
| | Check drive belt at 100,000 miles (150,000 km) or every 10 years | |
| ā | Check drive belt at 160,000 miles (240,000 km) or every 16 years | |
| Additional maintenance for convertible top Labor operation 03 70 00 | | |
| | Maintain and care for convertible top at 20,000 miles (30,000 km) or every 2 years | |
| Add | ditional maintenance 60,000 miles (90,000 km) or every 6 years Labor operation 03 83 00 | |
| | Replace drive belt | |
| | Change all-wheel drive controller oil | |
| | Replace fuel filter | |
| _ | | |
| Add | ditional maintenance every 120,000 miles (180,000 km) or 12 years Labor operation 03 88 00 | |
| | Change manual transmission oil | |
| | Change Tiptronic transmission oil and ATF filter | |
| | 0. 1 | |

| Every 2 years | | |
|---|--------------|--|
| ☐ Change brake fluid | | |
| Check roll-over protection system (911 Cabriolet only) | | |
| Every 4 years | | |
| Replace tire sealant | | |
| After 4, then every 2 years | | |
| ☐ Check battery for the tire pressure monitoring system | | |
| After 4, 8, 10, then every 2 years | | |
| ☐ Inspect airbag system | | |
| Assembly and running gear mounts: Visual inspection of all rubber/hydraulic mounts for damage | | |
| Inspection Performed - Technician Signature: | | |
| Road Test Check | | |
| Remote control, front seats, foot brake and parking brake (also or sion, ParkAssist, automatic speed control, PSM switch, PASM switch, | | |
| instruments: Check operation Oils, fluids: Visual inspection for leaks | | |
| Olis, Iluius. Visual Inspection for leaks | | |
| Road Test Performed - Technician Signature: | | |
| | | |
| Customer Name: | Date:/ | |
| VIN: WPO | | |
| Mileage (check one) Miles Kilometers: | | |
| Dealer Name: | Dealer Code: | |
| Repair Order #: | | |
| Technician Name: | | |
| Technician Signature: | | |