

Intermediate Maintenance Checklist – 911 Carrera/S/4/4S/Turbo/S (991) (2014-16)

Required Maintenance and Lubrication Service

| * Oil Change Every 10,000 miles (15,000 km) or 1 year. See Below Check Box. |
|--|
| ☐ Intermediate Maintenance (Labor Operation 03 14 00) See Technical Manual After 20,000, 60,000, 100,000, 140,000 miles etc. / 30,000, 90,000, 150,000, 210,000 km etc. Note: If the mileage for scheduled maintenance is not reached, intermediate maintenance must be performed no later than after 2, 6, 10 years. |
| The terms 'check' and 'inspection' include all necessary subsequent work such as adjusting, readjusting, correcting and topping off, but do not include repairing, replacing and reconditioning parts or assemblies. |
| Electrics |
| ☐ Diagnosis system: Read out fault memory; reset maintenance interval |
| ☐ Windshield wiper/washer system, headlight washer: Check function and nozzle adjustment |
| ☐ Horn: Check operation |
| ☐ Tires: Check tire pressure (TPM) |
| ☐ Batteries and ventilation hoses: Check condition |
| ☐ Electrical equipment as well as indicator and warning lights: Check operation |
| ☐ Check actuator travel of brake shoes (911 Turbo/Turbo S only) |
| Inside of Vehicle |
| ☐ Pollen filter: Replace filter element |
| Front Luggage Compartment |
| Pollen filter: Replace pre-filter element |
| Check front lid lock and safety hook of the front lid for secure seating and function properly |
| Windshield wiper/washer system, headlight washer: Check fluid level and antifreeze protection level |
| ☐ Check firewall body drains for debris |
| Outside of Vehicle |
| Check wiper blades |
| ☐ Vehicle lighting: Check operation |
| All headlights: Check adjustment |
| Radiators and air intakes: Visual inspection for exterior debris and blockage |
| Check the two Targa center bar drains for debris (911 Targa models only) |
| Under the Vehicle |
| ☐ Drain engine oil ☐ Tires: Check condition |
| ☐ Brake system: Visual inspection of the brake pads & brake discs for wear (w/o removing wheels) (Except PCCB) |
| □ Vehicles with PCCB: As of MY 2014, PCCB Brake discs must be checked for wear during every service and whenever brakes pads are replaced using special tool VAS 6813. Please refer to workshop manual for work procedure. □ Brake hoses and lines: Visual inspection for damage, correct routing and corrosion Check brake fluid level |
| Axle shafts: Visual inspection of the dust boots for leaks & signs of damage |
| Engine Compartment |
| ☐ Change oil filter and fill engine oil (Every 10,000 miles/15,000 km, see separate 0il Change Sheet, PNA 000 162 LC) |
| ☐ Coolant: Check level and antifreeze protection level |
| ☐ PDCC: Check fluid level |
| ☐ Check firewall body drains for debris |
| Additional Maintenance – Replace Spark Plugs (Labor Operation 03 81 00) |
| Replace spark plugs: every 40,000 miles / 60,000 km or 4 years (Except Turbo) |
| Replace spark plugs: 911 Turbo/Turbo S every 30,000 miles / 45,000 km or 4 years |
| Additional Maintenance - Drive Belt Labor operation 03 60 00 |
| Check drive belt at 40,000 miles (60,000 km) or every 4 years |
| Check drive belt at 100,000 miles (150,000 km) or every 10 years |
| ☐ Check drive belt at 160,000 miles (240,000 km) or every 16 years |
| Additional Maintenance - Convertible Top (Labor Operation 03 70 00) |
| ☐ Service and maintain convertible top: every 20,000 miles / 30,000 km or 2 years |
| |
| Additional Maintenance – Targa Roof (Labor Operation 03 71 00) |
| ☐ Service and maintain Targa roof: every 20,000 miles / 30,000 km or 2 years |

| Additional Maintenance every 60,000 miles / 90,000 km | or 6 years (Labor Operation 03 83 00) | |
|---|--|--|
| Replace PDCC reservoir | | |
| ☐ Replace drive belt☐ Change all-wheel drive controller oil (4-wheel drive models onl | 1.1 | |
| Change an-wheel drive controller on (4-wheel drive models on | у | |
| Additional Maintenance every 80,000 miles / 120,000 km or 4 years (Labor Operation 03 85 00) ☐ Ancillary unit mounts and chassis: visual inspection of all rubber mountings and boots for damage | | |
| Additional Maintenance every 120,000 miles / 180,000 | km or 12 years (Labor Operation 03 88 00) | |
| □ Manual transmission: change oil □ PDK transmission: change oil □ PDK transmission: change clutch oil □ All-wheel final drive: change oil (4-wheel drive models only) | | |
| | 1 00) | |
| Additional Maintenance every 2 years (Labor Operation 03 5 | 01 00) | |
| ☐ Change brake fluid (use only Original Porsche Brake Fluid)☐ Tire sealant (check expiration date and replace as necessary) | | |
| | | |
| Inspection Performed - Technician Signature: | | |
| | | |
| Road Test Check | | |
| Remote control, front seats, foot brake and electric parking br transmission, ParkAssist, cruise control, PSM, PASM & Sport s tion, heater, air-conditioning system and instruments: Check or | switches, sports exhaust system, door mirror fold-in func- | |
| Oils, fluids: Visual inspection for leaks | | |
| Road Test Performed - Technician Signature: | | |
| Customer Name: | Date:/ | |
| VIN: WPO | | |
| Mileage (check one) Miles Kilometers: | | |
| Dealer Name: | Dealer Code: | |
| Repair Order #: | | |
| Technician Name: | | |
| Technician Signature: | | |